

Elcometer 3540 Four-Sided Film Applicators

Can be used in accordance with: ASTM D 823-E



The **Elcometer 3540 Four-Sided Film Applicators** are easy to clean gauges manufactured to the highest accuracy.

The **Elcometer 3540 Four-Sided Film Applicator** is made from precision ground stainless steel with 4 thicknesses per applicator. The flat-edged prismatic body makes **Elcometer 3540 Four-Sided Film Applicators** suitable for coatings applied to a flat and relatively strong substrate. The 3540 Film Applicator can be used with the Elcometer 4340 Motorised Film Applicator.

Technical Specification

Part Number	Model	Film Thickness μm	Film Width* mm	Certificate
K0003540M001C	Elcometer 3540/1	50, 100, 150, 200	50	■
K0003540M002C	Elcometer 3540/2	50, 100, 150, 200	75	■
K0003540M003C	Elcometer 3540/3	50, 100, 150, 200	100	■
K0003540M004C	Elcometer 3540/4	50, 100, 150, 200	150	■
K0003540M005C	Elcometer 3540/5	50, 100, 150, 200	200	■
K0003540M006C	Elcometer 3540/6	50, 100, 150, 200	250	■

* Add 40mm to the Film Width to calculate the total width of the applicator

■ Calibration Certificate supplied as standard

Packing List

Elcometer 3540 Four-Sided Film Applicators

Instruction Manual

