BAMR Quality Control Instrumentation elcometer

Adhesion Testers

Cross Hatch Adhesion Tester



- Elcometer 107, 1540, 1542 Cross Hatch Cutters
- Instant assessment of the quality of the bond to the substrate - fast, low cost, visual comparison method
- Ideal for paint and powder coatings up to 250 microns - 1, 1.5, 2, 3mm spacing - 6 or 11 teeth
 - Conforms to ISO, AS, ASTM, BS, EN

Pull Off Adhesion Tester



- Elcometer 106,506,508,510 Pull Off Adhesion Tester
- Easy to operate, uses re-usable dolly 10-50mm
- Fully portable, measure on small, curved, flat surface
- Range: up to 100MPa, Accuracy: ±1% full scale
- Quick connect coupling field or lab tests
- Conforms to ISO, AS/NZS, ASTM, BS, EN, NF, DIN

Climatic Condition Testing

Climate Condition Monitor

Infra Red Temperature



- Elcometer 319 Dew Meter Standard & Top models
- Air Temperature, Relative Humidity (RH), Surface Temperature, Dewpoint Temperature, Data Logger
- DeltaT-difference between dewpoint & surface temp
- Bluetooth / USB output to free ElcoMaster Software

Hygro Thermometer



- 8706 Hygro Thermometer Air Temperature, Relative Humidity (RH), Dewpoint Temperature, Wet Bulb
- M20 Low Cost Hygro Thermometer RH & Temp
- Elcometer 116 Whirling / Sling Hygrometer
- Protimeter BLD7751 Hygromaster 2- download to PC

Temperature



- Elcometer 214L, 8889 Infrared Temp Guns
- Non contact temperature gauges with laser pointer
- Range: -40 to 500°C for the most popular 8889
- Accuracy: ±2%, Resolution: 0.1°C, 10:1 D:S



- Elcometer 113, 212, 213-2 Temperature Gauges
- Air, Surface, Liquid Temperature, Limpet Magnetic
- Range: -50 to 1370°C various probe options
- Accuracy: ±1% or 1°C, Resolution: 0.1 to 1°C

Coating Thickness Gauges

Dry Film Thickness - Digital



- Elcometer 456 Coating Thickness & 311, 415, 355
- >70 rdgs/min, new scan mode >140 in Auto Repeat
- Separate, Miniature, HighTemp, Armoured Probes
- Accuracy: ±1 to 2%, Range: 0 31mm, Trend Graph
- USB / Bluetooth output: 150,000 rdgs, 2500 batches
- Upgradeable Firmware, 2 yr Warranty, IP64 rating
- Conforms to ISO, AS, ASTM, BS, DIN, SSPC, IMO

Dry Film Thickness - Coating on Concrete



- Elcometer 500 Coating Thickness Gauge for ultrasonic non-destructive coating thickness measurement on Concrete & other similar substrates
- Accuracy: 2%; Range: 150µm to 10mm
- 60 rdgs/min, >140 in scan mode
- USB / Bluetooth output: 100,000 rdgs, 1,000 batches
- Signal strength indicator- accurate & reliable readings
- Rugged, ergonomic probes field replaceable

Dry Film Thickness - Destructive



- Elcometer 121/4 Paint Inspection Gauge (PIG), 141
- Used for non metallic substrates eg wood, plaster, plastic and for determination of multilayer coatings.
 - · Conform to ISO, AS, ASTM, BS, DIN, ECCA, EN

Dry Film Thickness - Mechanical



- Elcometer 211 Magnetic DFTG Banana Gauge
- Ideal for hazardous and dangerous environments
- Can be used under water Accuracy: ±5%, 0-1000µm
- · Conforms to ISO, AS, ASTM, BS, DIN, SSPC, NF

Dry Film Thickness - Standards



- Elcometer 990 Calibration Foils / Shims to ISO
- Accuracy: 1%, Range: 12mic to 20mm
- Used in the laboratory and on site
- Ideal method for accurately calibrating DFT Gauge
- Used with 990 Zero Test Plates

Dry Film Thickness - Software



- Free ElcoMaster for 456,224,319,130,MTG8,480,500
- User friendly, create professional reports in **seconds**
- For PC and Mobile use customised reports for all applications - insert logos, images, GPS co-ordinates
- Save data to Cloud for access anywhere in the world

Wet Film Thickness Combs



- Elcometer 112, 115, 3236, 3238, 154 WFC's
- Quick, easy method of measuring coating thickness
- Plastic, Aluminium or Stainless-Steel Combs
- 2, 4 or 6 sided combs
- Conforms to ISO. Range: 25 to 3000µm

Wet Film Thickness Wheels



- Elcometer 3230 Wet Film Wheels / Coil Coating
- high precision, accurate and easy to use
- Set of three wheels, central wheel is of a smaller diameter and is eccentric relative to the two outer wheels - Stainless-Steel
- Conforms to ISO / ASTM. Range: 0 to 1000μm

Concrete Testing

Concrete Covermeters / Rebar Locators



- Elcometer 331 Basic, Standard, Top, Kolectric 8022
- Rebar detection, orientation, depth, diameter
- Also potential for corrosion with Half Cell
- Download readings to PC, Conforms to ISO
- Accuracy: ±1mm, Range: 0 to 180mm

Concrete Adhesion

Concrete Moisture



- Elcometer 506, 510 (Automatic)
- Elcometer 106/6 adhesion of Coatings on Concrete
- Special 50mm diameter dollies for rough surfaces
- 106/6: Hand operated, 506,510: Smooth Pull Rate
- Range: 106/6: 0 to 3.5 MPa; 506 & 510: 0.3 to 4 MPa

Concrete Hardness / Test Hammer



- Low Cost HT225A Concrete Compression Test Hammer / (Schmidt equivalent) - with certificate
- Elcometer 181 Mechanical,182 Digital Test Hammer
- Quick & easy to use, 182 downloads readings to PC • Non-destructive method of testing concrete insitu

- Concrete Moisture Encounter (CME5) specifically designed for flooring industry - no drilling required
- Range: 0 to over 6% Depth: 12.5mm non-destructive DM4A Moisture Meter digital non-destructive meter
- Moisture Measurement System MMS for RH as well



Coating Physical Test Equipment

Abrasion, Washability & Brushability




- Elcometer 1720 Abrasion, Scrubbing, Washability
- To test paint, lacquers, inks, coatings & much more
- Wide range of tools available- flat & curved samples
- Elcometer Taber 5750 Linear Abraser and 5135 & 5155 Abrasers - regarded as the industry standard
- Conforms to ISO, AS, ASTM, DIN, EN, GME, PSA

Drying Time & Permeability



- varnish, plastic, cellophane, etc



Film Application & Test Charts



- Elcometer 4340 Motorised Automatic Film Applicator
- Elcometer 3520 Baker Film Applicators, 4360 & 4361 Spiral Bar Coaters / Draw Down Bars
- Cube Film Applicator, Multiple Gap, with reservoirs
- Wide range thicknesses & widths, Vacuum Tables
- Leneta / Opacity Test Charts full range available

Balances / Density



- Elcometer 8720 KB Balance
- Low cost easy to use. Range 0 10100g
- Elcometer 1800 Densimeter / Picnometer / Specific Gravity Cup - 50cc or 100cc, Optional Certificate
- Stainless steel precision instrument for determining the specific weight of paints and similar products

Elasticity & Resistance Deformation



- Elcometer 1510, 1500, 1506 Mandrel Bend Testers
- Elcometer 1620 Cupping Test
- Elcometer 1615 Variable Impact Testers
- Used for testing elasticity, adhesion, elongation & cracking of paint on sheet metal & impact resistance
- Conforms to ISO,AS,ASTM,BS,DIN,ECCA,JIS,NFT

Fineness of Grind Gauges



- Elcometer 2020 Hegman North Grind Gauge
- Elcometer 2050 High Precision Grindometer
- Elcometer 2070 NPIRI Fineness of Grind Gauges
- Used to determine particle size and fineness of grind of many materials, including: paints, pigments, inks, coatings, chocolates or other similar products
- Conforms to ISO, AS, ASTM, DIN, EN, FTMS, NF

Distance & Levels

Laser Distance Meters



- Leica Disto Laser Distance: D1, D110, D2, X3, X4, D510, D810 & S910 - Accuracy: ±1mm
- Range: 0 to 40, 60, 100, 120, 150, 200 & 300m
- Pythagoras function heights, Tilt sensor for angles
- D1, D110, D510, D810, S910- Bluetooth connection
- Shortcut keys for addition, subtraction, area, volume
- Digital Pointfinder (4X zoom), large 2.4" colour display
- NEW Intrinsically safe NVI00-1S hazourdous envir.

Levels



- Digital Inclinometer 360° Angle Gauge Module measures Angles in Degrees or Slopes in %
- Various rail lengths: 250, 600, 1000mm.
- Also Module supplied on it's own
- Accuracy to 0.1 for all Angles
- LCD display operates through 0 to 360°

Gloss

Glossmeters



- Elcometer 480 Gloss Meters are small, robust & ergonomic, easy to use, highly accuracy, repeatable & reproducible - 3 - 10 readings per second
- Multiple angles; 20°, 60°, 85° 40,000 reading memory in up to 2,500 batches, USB & Bluetooth®
- · Auto calibration tile recognition via RFID

• Rhopoint Novo-Gloss IQ Image Quality, Haze,

Haze / Distinctness of Image (DOI) / Goniophotometer

- Distinctness of Image (DOI), Goniophotometer
- The instrument profiles complete specular reflectance and calculates gloss, peak specular reflectance, Distinctness of Image (DOI) and Reflection Haze
- The Novo-Scan IQ can achieve similar results to the Wavescan at a fraction of the price

Shade / Reflectometer

- Rhopoint Novo-Shade Duo+ Reflectometer/Opacity
- Measures shade and opacity with 45/0° geometry
- · Automatic calibration mode. 2 year warranty
- · Continuous-read feature for large surfaces
- Includes Novo-Soft[™] for download to computer
- Conforms to ISO, ASTM, DIN & FTMS

Colour

- Elcometer 6210 RAL Colour reference charts Colour collection of RAL CLASSIC Colours
- Elcometer 6300 Colour Cabinet view samples to maintain colour consistency and quality
- Conforms to ISO, AS, ASTM, BS, SAE, TAPPI, NF

Hardness

Hardness of Metals



- TH5100 Integrated Portable Hardness Testers
- Automatic identification of impact test direction
- Compact, high accuracy, wide measuring range and simplicity of operation with digital readout
- Hardness Scales HLD, HB, HRC, HRB, HV, HS

Concrete Hardness / Test Hammer



- Low Cost HT225A Concrete Compression Test Hammer / (Schmidt equivalent) - with certificate
- Elcometer 181 Mechanical, 182 Digital Test Hammer
- Quick & easy to use, 182 downloads readings to PC
- Non-destructive method of testing concrete insitu



- Elcometer 3101 Barcol Impressor Portable Hardness Tester - aluminium, copper, brass, plastic, fibre-glass
- Shore A & D, TH5431 Shore Durometers / Hardness Testers for soft & hard rubber & plastic

Hardness - Coatings



- Elcometer 3080, 501 Pencil Hardness Tester
- Elcometer 3092 Sclerometer, 3000 Clemen Unit
- All for testing Hardness & Scratch resistance
- Conforms to ISO, AS, ASTM, DIN, EN, GME, PSA



Inspectors Accessories

Coatings Defects Manuals / Publications



· Elcometer Fitz Atlas 2 of Coating Defects - reference manual with over 180 colour photographs to help the site inspector identify coating failures

Magnifiers & Microscopes



- 139 Illuminated Pocket Microscope 30x / 60-100x
- Elcometer 131 Telescopic Inspection Mirrors-150cm
- Elcometer 137 10x Illuminated Magnifier-scaled lens
- Elcometer 7210 30x Microscope ideal for defects
- Elcometer 900 50x Concrete Crack Microscope
- · Various magnification and ranges

Inspectors Accessories - Other



- Elcometer 147 Weld Gauge angle of preparation, high - low, fillet weld throat & length
- Elcometer 144 Paint Safe Marker Pens

Inspectors Accessories - Other



- Elcometer 132 Torch / Flashlight Intrinsically safe
- Elcometer 143 Crack Width Ruler simple low cost
- Pocket Real Estate Master calculator

Laboratory Instruments

Oven Temperature Logger



- Elcometer 215 Oven Temperature Data Recorder including Software 260k readings, Thermal Barrier
- Easy to use, measure & record the oven temp profile
- Large display for easy menu-driven operation
- Displays result of every stored batch, incl Cure-index
- Accuracy: 1°C, Res: 0.1°C, Range: -200 to 1300°C
- USB connection to FREE ElcoMaster Software

Measuring Instruments

Anemometer



- 8910, Elcometer G410 Anemometer / Air Flow / Velocity / Air Speed Meter
- Accuracy: 2%, 0.6°C. Resolution: 0.01ms, 0.1°C
- Range: 0.4 to 35 ms, -10 to 50°C
- 8910 Wind Speed, RH, Dew Point, Windchill, Altitude, Heat Index, Barometric Pressure

Vibration



- TV7120 and TV7126 Portable Pen Type Vibration Tester - ideal for quick test of bearings and gears
- TV7231 Portable Vibration Tester with full graphic LCD & Spectrum Analysis, 3 display modes, RS232

Metal Detection / Locators

Rebar Locators and Covermeters



- Elcometer 331 Concrete Covermeter Basic, Standard & Top, Kolectric 8022 CoverMeter
- Allows identification of location, orientation, depth and diameter of rebar & the potential for corrosion
- Conforms to ISO, AS, ASTM, BS, DIN, TR, UNI

Wall Tie and Stud Locators



- MT6 Metal Locator / Detector finds non-ferrous & ferrous metal
- Depth: 152mm & indication of depth MultiScanner Pro SL Stud Locator

Industrial Metal Detectors



- Elcometer P500 Imp Box locator. Depth: 1 meter
- Simple to use and very rugged
- Detects Manholes, Valve Boxes, Stakes, Nails

Pipe and Cable Locator



- Leica DD220 & DD230 Smart Utility Locators
- Industry-leading digital signal processing to identify underground assets
- Scalable & designed with Bluetooth technology, providing a wire-free connection to mobile devices

Inspection Kits

Digital Inspection Kits



- Elcometer Digital Basic and Top Kits 4 models
- Portable, and conveniently stored in a hard, plastic case- Top models download readings to ElcoMaster
- Elcometer 319 Climate Gauges with logging
- Elcometer 224 Surface Profile Gauges
- Elcometer 456 Coating Thickness Gauges
- · Separate models enable you to carry out multiple tests at a time

Protective Coating Inspection Kits



- Elcometer Protective Coating Inspection Kits 6 Kits
- Comprehensive kit incorporating all key gauges and inspection accessories conveniently stored in a hard, plastic case.
- Measurement options include: Material Thickness, Surface Inspection, Weld Inspection, Surface Cleanliness, Surface Profile, Climatic Conditions, Coating Thickness, Adhesion & Pinhole Detection.

Elcometer Blasting Inspection Kit



- The Elcometer Blasting Inspection Kit is a surface preparation inspection kit providing a range of inspection equipment to test surface profile and surface contamination of blasted profiles.
- Other Kits include: Elcometer Protective Inspection Kit for Hazardous Areas, Surface Contamination, Coatings on Concrete Inspection Kit

Elcometer Qualicoat Powder Coating Inspection Kit



- The Qualicoat Organisation brings together the ideals of several national coating associations into one quality label for the powder coating applied to aluminium architectural applications
- Also a Powder Coating Inspection Kit
- Other Kits include: Automotive Inspection, Elcometer **Duct Deposit Measuring System**



Moisture

Building Materials



- Surveymaster Moisture Meter is a Digital dual mode unit - Search (20mm deep) & Measure (Pin) options
- Moisture Encounter Plus (ME5) Moisture Meter
- Range: from 5 to 30% actual Moisture % 0 to 100% Relative Scale, Depth: 20 & 30mm

General Purpose



- Popular Low Cost Mini 2000 Pin Moisture Meter
- Speedy Ashworth Calcium Carbide Moisture Meter
- Moisture Measurement System (MMS) Dampness Diagnosis Kit - Measure, Search, Hygrometer, Infrared Mode, USB output and Logging function

Paper / Cardboard



- DM4A Moisture Meter digital non destructive universal moisture meter for measuring moisture in paper, cardboards, also wood, building materials
- Range: 0-50% (adjust.) Res: 0.1%. Depth: 30mm
- Also RS232 Output to PC

Wood



- Timbermaster Moisture Meter is a simple to use digital pin type moisture meter with Heavy Duty probe
- It has 8 in-built calibration scales for ease of use
- Range: 6% to 90% Resolution: 0.1% Depth:10/30mm
- DM4A, ME5, Mini 2000, Digital Mini Moisture Meter



- Concrete Moisture Encounter (CME5) specifically designed for flooring industry - no drilling required
- Range: 0 to over 6% Depth: 12.5mm non destructive
- DM4A Moisture Meter digital non-destructive meter
- Moisture Measurement System MMS for RH as well

Agriculture / Bales / Tobacco / Grain



- Digital Balemaster Meter with 600mm probe for Bales
- Very popular in the tobacco industry as well
- Grainmaster "i2" Digital Moisture Meter with Grinder
- Accurate, repeatable, and pre-programmed with 15 crop calibrations, 1year warranty

Non Destructive Testing NDT

Ultrasonic Flaw Detection Gauges



- FD700DL small, powerful, fast, accurate hand-held flaw detectors - ideal for weld inspection & forgings
- A & B-Scan displays to flaw detection modes such as TRIG, DAC, TCG, Flank and Peak
- Large data storage with multiple formats: Alpha numeric grid and sequential w/auto identifier

Corrosion / Precision Thickness Gauges



- CG70, CG100 Corrosion Thickness with A & B scans
- Range: 500mm, High speed scan mode: 32 / second
- PTG6, PTG8, PG70ABDL- 0.01or 0.001mm resolution
- Range: 0.15 to 25.4mm, ideal for thin materials
- A, B scans, Data Logging, Scan Mode, Adjustable gain, Limit Alarm, Gates, Differential mode

Pinhole / Porosity Detection

Sponge / Pinholes



- Elcometer 270 Sponge / Pinhole Detector 9 & 90V
- High quality, low voltage detector coating <500μm
- · Accessories: sponge sizes, roller wands, telescopic
- Inspection Kit with all accessories available
- Conforms to ISO, BS, EN, ASTM, NACE, RP

Spark / Holiday



- Elcometer 266 & 280 High Voltage Holiday Detector
- 3 ranges: 0 to 5, 15 or 30kV, extra safety features
- Accessories for various applications rolling springs for external pipeline inspection, extension handle
- 280 ideal for pipelines no signal return cable req.

Surface Preparation

Surface Profiles - Blasted



- Elcometer 224 Digital Basic, Top Bluetooth / USB link to ElcoMaster – measure on convex surfaces
- Elcometer 123 Analogue Surface Profile Gauge
- Elcometer 122 Testex Tape & 124 Dial Gauge
- Elcometer 125 Comparators, 119 Pipe Pit Gauge

Surface Cleanliness – Soluble Salt Profiler



- Elcometer 130SSP Soluble Salt Profile Salt Meter
- Generates full colour salt density maps in 2D or 3D
- Gives you a Bresle equivalent reading link to PC
- Elcometer 130 Salt Contamination Meter
- Soluble Salt Meter SSM easy use, no consumables

Surface Profiles – Machined / Roughness



- TR3110/3200 Portable Digital Machined Roughness
- Accurate, portable, hand held, pocket sized
- Elcometer 7062 Marsurf Surface Roughness Tester with various pickup extensions and software
- Elcometer Rubert and Rugotest Comparators

Surface Cleanliness



- Elcometer 138 Bresle Kit & Elco 135 Bresle Patches
- Elcometer 134 CSN- Chlorides, Sulphates & Nitrates
- Elcometer 128 Pictorial Surface Stds, Amine Blush
- Elcometer 142 Dust Tape Test Kit to ISO 8502-3

Ultrasonic Material Wall Thickness

Low Cost popular models



- TT2110, TT2130, SA40 Ultrasonic Wall Thickness
- Popular hand held digital instruments to measure material thickness of materials from one side only
- Accuracy: ±1%. Range: 0.8 to 225mm
- Resolution: 0.01mm, Download to PC with TT2130
- · High Temp and various frequency probes available

Elcometer Range



- Elcometer Ultrasonic Material Thickness Gauges MTG 2, 4, 6DL, 8BDL downloads to ElcoMaster
- Accuracy: ±0.01mm. Range: 0.63 500mm
- Echo to Echo mode for measuring thru' coatings
- Easy to use menu driven wide range of transducers
- MTG8BLD B-Scan cross sectional display

Viscosity and Consistency

Viscosity - Flow and Dip Cups



- Elcometer Viscosity Cups: Quick, easy, low cost method, measure consistency of paints, varnishes
- Ford 4 most popular, ISO, ASTM, FORD, AFNOR, NFT, DIN, NF, EN, NBN, BS all available
 - Frikmar, Zahn, Shell, Lory, Daniel Flow cups
 - · Viscosity Oils for calibration available

