

Elcometer 3508 & 3560 4 Gap Applicator with Reservoir

Can be used in accordance with:
ASTM D 823-E (Elcometer 3560 only)



The Elcometer 4 Gap Film Applicators are precision engineered from hardened stainless steel to provide four film thicknesses in one gauge.

Simply rotate the applicator to the required thickness, fill the reservoir with the test coating and draw down a uniform stripe.

The Elcometer 3508 is supplied with two reservoirs, ideal for preparing samples for the Elcometer 1720 Abrasion and Washability Testers or for comparing two coatings simultaneously.

Technical Specifications

Part Number	Model	Film Thickness µm	Film Width* mm	Certificate
K0003560M201	Elcometer 3560/1 4 Gap Applicator with Reservoir	30, 60, 90, 120	60	o
K0003560M202	Elcometer 3560/2 4 Gap Applicator with Reservoir	50, 100, 150, 200	60	o
K0003508M001	Elcometer 3508/1 4 Gap Applicator with Reservoir	100, 150, 200, 250	2x50	o

* Elcometer 3560 total width: 90mm; Elcometer 3508 total width: 165mm
o Optional Calibration Certificate available

Packing List

- Elcometer 4 Gap Applicator with Reservoir
- Storage Case
- Operating Instructions

