

Elcometer RIGA Horizontal Bellows



Multi spray gun feeding capabilities, the powerful Elcometer Riga is an air assisted airless horizontal bellows pump with a smooth bellows action for uniform material flow. Precision engineered and designed for handling of shear sensitive, moisture-sensitive materials and UV coatings, the Elcometer Riga range is ideal for automated paint lines where performance, reliability and coating stability matter most.

Smooth internal paint flow

Ideal for flat bed coating systems, the gentle bellows action of the Elcometer Riga pump prevents paint bubbling of sheer sensitive materials such as varnishes UV-cure coatings, high-solid waterborne and solvent based materials.

Durable and reliable

With minimal working parts to replace, the tough stainless steel and aluminium construction of the Elcometer Riga provides long-lasting durability with minimal maintenance, even for highly demanding materials.

Enclosed bellows system

The Elcometer Riga ensures no air or moisture contamination - ideal for moisture sensitive coatings even when if it fails, thanks its closed system with no exposed seals or packing.

Easy to use and maintain

Elcometer Riga bellows pumps are easy to operate and simple to maintain.

Key features

1)	Low maintenance 59cfm air motor for large, automated paint lines
2)	Pump fluid section manufactured from stainless steel to handle solvent & water-based coatings
3)	High flow 9.75lpm engineered to supply multiple guns
4)	Smooth bellows action for uniform paint flow, engineered for use with sheer sensitive coatings
5)	Anti-pulse fluid filter fitted as standard ensures constant spray pattern and uniform film thickness
6)	Fluid and air regulator included as standard for consistent control of fluid & air pressure
7)	Each pump is fitted onto a rugged & ergonomic trolley with built in hose & gun rack, for easy movement around site - unbolt the bracket and pump from the trolley to wall mount.



The Elcometer Riga is suitable for use with:

	Product	
Pre-catalysed wood lacquers	Acid catalyst wood lacquers	Waterborne wood lacquers
Exterior joinery coatings	Fire retardant class b-s1, d0 coatings	Fire retardant acid catalyst wood lacquers
Floor lacquers	Single component (1k) epoxies	Single component (1k) polyurethanes
Anti-fouling (1k) low viscose coatings	Water based enamel	Military grade bio grade coatings





Sound deadener coatings UV Curable wood coatings Solvent based polyurethane coatings Moisture sensitive polyurethane coatings

Epoxy primers UV Curable polyurethanes

Upgrade to Elcometer Riga Packages







1. Elcometer Riga Pumps				
The range of Elcometer Riga pumps				
are available wall or trolley mounted				
supplied with a fluid regulator and				
suction hose as standard. Hoppers can be purchased separately.				
can be parenased coparatory.				

1. Air and Product Hose 7.5m Combined Anti-Static Air & Product Hose with Protective Cover for Air Spray (Low Pressure) Systems.

3. Sagola V7 Mix Sagola V7 Mix Automatic Air Assisted Airless Spray Gun with a choice of needle aircap, and nozzle combinations to suit your application.

Technical Specifications

	RIGA H10	RIGA H15	RIGA H25	RIGA V25	
Ratio	10:01	15:01	25:01:00	25:01:00	
Maximum fluid particle size**	0.25mm	0.25mm	0.25mm	0.25mm	
Fluid temperature range	4.4 - 60°C	4.4 - 60°C	4.4 - 60°C	4.4 - 60°C	
Fluid inlet size	Metric 36 x 2 (Male)	Metric 36 x 2 (Male)	Metric 36 x 2 (Male)	3/4" BSP Male	
Fluid outlet size	1/4" BSP Male	1/4" BSP Male	1/4" BSP Male	1/4" BSP Male	
Seats	Stainless Steel	Stainless Steel	Stainless Steel	Polyamide	
Balls	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	
Pump Body / Cylinder Housing	Aluminium	Aluminium	Aluminium	Aluminium	
Centre Section	Hard Chrome Stainless Steel	Hard Chrome Stainless Steel	Hard Chrome Stainless Steel	Hard Chrome Stainless Steel	
Packing Kit (Top)	Polyethylene, Stainless Steel	Polyethylene, Stainless Steel	Polyethylene, Stainless Steel	Polyethylene, Stainless Steel	
Packing Kit (Bottom)	-	-	-	Polyethylene, Stainless Steel	
Pump Body / Cylinder Housing	Aluminium	Aluminium	Aluminium	Aluminium	
Air Pressure Operating Range	1-6bar	1-6bar	1-6bar	1-7bar	
Air consumption at 60 bar & 2.4 CPM	16.71lpm	13.85lpm	14.96lpm	-	
Air consumption at 100 bar & 5.7 CPM	-	-	-	24.31lpm	
Maximum Air Inlet Pressure	6bar	6bar	6bar	7bar	
Air Inlet	1/4" BSP Female	1/4" BSP Female	1/4" BSP Female	1/4" BSP Female	
Air Exhaust / Silencer Port	1/4" BSP Female	1/4" BSP Female	1/4" BSP Female	1/4" BSP Female	
Minimum compressor requirements	16.71lpm	13.85lpm	14.96lpm	24.31lpm	
Ambient Air Temperature Operating Range	-10 - 60°C	-10 - 60°C	-10 - 60°C	-10 - 60°C	
Maximum Fluid Outlet Working Pressure	66bar	82bar	148bar 176bar		
Stroke Length	42mm	42mm	42mm	44mm	
Maximum Spray Tip Size	-	-	-	0.45m	





Product Output per Cycle	105.55 cc	105.55 cc	105.55 cc	42.33 cc
Free Flow Delivery @ 60 CPM*	9.75 lpm	9.75 lpm	9.75 lpm	2.54 lpm
Weight (Pump only)	24kg	25kg	31kg	9.7kg
Weight (Wall Mount with Suction Hose)	26.3kg	27.3kg	33.3kg	12kg
Weight (Cart Mount with Suction Hose)	37.5kg	38.5kg	44.5kg	24.5kg
Dimensions (Cart Mount)	543 x 527 x 999mm	543 x 527 x 999mm	543 x 527 x 999mm	439 x 490 x 999mm
Dimensions (Wall Mount)	543 x 359 x 516mm	543 x 359 x 516mm	543 x 359 x 516mm	332 x 294 x 527mm

Package Selector

	Pump				Spray Gun					
Part Number	Wall Mount	Trolley & Wall Mount	Suction Hose	Hopper Fed	7.0m Air & Product Hose ₁	Anti-pulse chamber	Sagola Mini Xtreme Mix Spray Gun	Sagola V7 Mix Standard Automatic Spray Gun	Sagola V7 Mix Robotic Automatic Spray Gun	Spray Tip
RIGA H10										
RH10-MXM-1340			•			•	•			13/40
RH10-MXM-1140			•							11/40
RIGA H15										
RH15-MXM-1340			•				-			13/40
RH15-MXM-1140			•							11/40
RIGA H25										
RH25-MXM-1340							-			13/40
RH25-MXM-1140		-				•	•			11/40
RH25-V7S-1340								Standard		13/40
RH25-V7R-1340									Robotic	11/40
RIGA V25										
RV25-MXM-1340			•		•					13/40
RV25-MXM-1140		•	•				•			11/40

Dart Numbers

Fait Numbers			
Elcometer Riga H10 Air Ass	Part Number:	ston Spray Pump PSPBH10AAA-T	
Elcometer Riga H15 Air Ass	isted Airless Bellows Pi	ston Spray Pump	
	Part Number:	PSPBH15AAA-T	
Elcometer Riga H25 Air Ass	isted Airless Bellows Pi	ston Spray Pump	



With suction hose or deposit and pump output filter.
 Product Output per Cycle = Fluid Displacement per Cycle
 Maximum values with water as test media.









	Part Number:	RH25-V7R-1340
ccessories		
ombined Air & Product	t Hose with Protective Cov	er: 7m
	Part Number:	PT56414036
SAGOLA WORLD TO MANY MANY MANY MANY MANY MANY MANY MANY		
ombined Air & Product	Hose with Protective Cov	
MAGUA SE MANUA MEN AND AND AND AND AND AND AND AND AND AN	Part Number:	PT56414037
	with 8mm Quick Connect 0.011"/0.28mm, 40 Degre	Air Coupling and 1/4" Swivel Product Coupling, with Air Assisted
ness Spray rip 11/40.	Part Number:	PG35130202
	x with 8mm Quick Connection 0.013"/0.33mm, 40 Degre	ct Air Coupling and 1/4" Swivel Product Coupling, with Air Assiste
mess opidy rip ro/40.	Part Number:	PG35130206
agola V7 Mix Standard	l Automatic Spray Gun with	n 13/40 Spray Tip
	Part Number:	PG35230101
agola V7 Mix Robot A	utomatic Spray Gun with 1	3/40 Spray Tip
agola vi mix Robot At	Part Number:	PG35230102

