

Dakota Ultrasonic Couplant



The Dakota Ultrasonic Couplant is a viscous gel that has been designed to work on both horizontal and vertical surfaces. Dakota has developed a viscous gel to work on both horizontal and vertical surfaces. The temperature range for regular couplant is -15 to 104°C. The Elcometer high temperature gel has a range of up to 398°C for use with high temperature transducers.

Technical Specification

Part Number	Description	Suitable For														
		ZX Range	MX Range	CMX Range	PZX	PMX	PMX4	R9	PR8-DL	UX2	FX70	FX71	FX80	FX81	BT1	BT2
V-000-0001	Ultrasonic Couplant; 120ml bottle	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
V-000-0002	High Temperature Ultrasonic Couplant; 60ml	■	■	■							■	■	■	■		
V-000-0003	Ultrasonic Couplant; 360ml bottle	■	■	■	■	■	■	■	■		■	■	■	■	■	■
V-000-0004	Ultrasonic Couplant; 4.5L	■	■	■	■	■	■	■	■		■	■	■	■	■	■
V-000-0005	Ultrasonic Couplant; 120ml Low Viscosity														■	■
V-000-0007	Underwater Gasket Lubricant – 6g									■						
A-185-0001	O-Ring kit (1-lubricant, 2-gaskets)									■						

Part Numbers

Part Number	Description
V-000-0001	Ultrasonic Couplant; 120ml bottle
V-000-0003	Ultrasonic Couplant; 360ml bottle
V-000-0004	Ultrasonic Couplant; 4.5L
V-000-0002	High Temperature Ultrasonic Couplant; 60ml
V-000-0007	Underwater Gasket Lubricant – 6g
V-000-0005	Ultrasonic Couplant; 120ml Low Viscosity
A-185-0001	O-Ring kit (1-lubricant, 2-gaskets)